

MDM2250

Cellular Modem

MDM2250 is an industrial-grade USB LTE Cat 4 Quad-band modem with a rugged housing and an external antenna for better signal coverage. This product is perfect for upgrading existing industrial equipment with cost-efficient LTE connectivity.



m2mLOGGER®
remote monitoring eco-system

Technical Specifications

GENERAL

Connectivity	GSM/GPRS (4G) Quad Band FDD LTE, TDD LTE, TDSCDMA, WCDMA CDMA2000 1x/EVDO, GSM (900/1800MHz)
Interface(s)	1 x microUSB
SIM	1 x 3FF (Micro SIM)
Voltage	9-24VDC VDC $\pm 10\%$
Power	10W (peak)
Protection	Surge protection on microUSB Output Over voltage and reverse polarity protection on Power Input

STATUS INDICATION

Power, Net Status, Net Mode

ENVIRONMENTAL

Operating Temperature	0 to 55 °C
Humidity	5 to 95% RH (non-condensing)

PHYSICAL

Dimensions	45 x 75 x 46 mm
Mounting	DIN Rail
Weight	100 gms approx.
Color (RAL)	Black (9005)
Material	ABS

Accessories

POWER SUPPLY

AC-DC Ultra slim DIN rail power supply
Input: 85-264VAC, Output: 12VDC @ 2A



Email sales@m2mlogger.com
Web www.m2mlogger.com



M2MLogger

An ISO 9001:2015 Certified Company

HEAD OFFICE

Plot 67, Street 1-B,
Friends Colony Industrial Area,
Shahdara, Delhi - 110095
INDIA

WORKS

B-8, First Floor
F.I.E. Patparganj Industrial Area
Delhi - 110092
INDIA